

MiRHook (200) for automated in-house cart transport solutions

MiRHook 200 EN 03 2017

Specifications	
Designated use	Mobile robot with hook for fully-automated pick-up and delivery of carts
Dimensions	
Length	1275 to 1180 mm (hook lowest to highest positions)
Width	600 mm
Height	550 to 900 mm (hook lowest to highest positions)
Height above floor	Robot: 50 mm; Gripping height: 50-390 mm
Weight (without load)	97 kg
Color	RAL 7011
Towing capacity	
Load on cart	Up to 500 kg at <1% incline - 300 kg at 5% incline
Speed and performance	
Running time	8-10 hours or 15-20 km (depending on load)
Maximum speed	1.1 m/s (4 km/h)
Turning radius (without cart)	520 mm (around center of robot)
Swinging radius (with cart)	Total length of robot and cart plus 550 mm
Positioning accuracy (placing cart)	+/-200 mm from center of position, 10° accuracy
Power	
Battery	Li-NMC, 24 V, 40 Ah; charging time: up to 3 hours (0-80%: 2 hours)
Internal charger	Input: 100-230 V ac, 50-60 Hz / Output: 24 V, max 15 A
Environment	
Ambient temperature range	+5°C to 50°C (humidity 10-95% non-condensing)
IP class	IP 20
Communication	
WiFi	Dual-band wireless AC/G/N/B
Bluetooth	4.0 LE, range: 10-20 m
I/Os	USB and Ethernet
Safety sensors	
SICK laser scanners S300 (2 pcs.)	360° visual protection around robot
3D camera Intel RealSense™ on robot	Detection of objects ahead 50-500 mm above floor
3D camera Intel RealSense™ on front of hook	Detection of objects ahead up to 2000 mm above floor
Ultrasonic scanners (4 pcs.)	Detection of transparent objects ahead, e.g. glass doors
Cart	
Length	500 to 2400 mm
Width	400 to 1500 mm
Height	200 to 2000 mm

Copyright © 2017 Mobile Industrial Robots ApS. All rights reserved

Mobile Industrial Robots ApS
Emil Neckelmanns Vej 15F
DK-5220 Odense SØ

+45 20 377 577
mail@mir-robots.com
www.mirrobots.com



MIRHook 200 dimensions

MIRHook 200 EN 03 2017

